

## Specification Sheet

Part Number: 151-00180



Connector Clip; Hole Dia. 6.2X12.2mm; Panel 0.6-6.0mm/ PA66HIRHS; Black; 1000/Pack

Article Number	151-00180
Type	YCCFT62x122
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>•Head design contains clamping rails to provide full circumferential compression around bundles.</li><li>•Bent tail allows for quick insertion into head.</li></ul>
Quantity Per	pcs.
Product Description	Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.
Short Description	Connector Clip; Hole Dia. 6.2X12.2mm; Panel 0.6-6.0mm/ PA66HIRHS; Black; 1000/Pack

Global Part Name

YCCFT62x122-PA66HIRHS-BK

Length L (Imperial)

0.83

Length L (Metric)

21.08

Fixation Method

Fir Tree for oval holes

Width W (Imperial)

0.63

Width W (Metric)

16.0

Height H (Imperial)

0.71

Height H (Metric)

18.0

Panel Thickness Min(Imperial)

0.02

Panel Thickness Max(Imperial)

0.24

Panel Thickness Min (Metric)

0.6

Panel Thickness Max (Metric)

6.0

Mounting Hole Diameter D (Imperial)

0.24 x 0.48

Mounting Hole Diameter D (Metric)

6.2 x 12.2 mm

Mounting Hole Diameter D Min (Imperial)

0.244

Mounting Hole Diameter D Max (Imperial)

0.48

Mounting Hole Diameter D Max (Metric)

12.2

<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3926909987
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	1.18