



Conductor: [26AWG(0.16/7)Bare Copper]x8C
 Insulation: [PP6331 ID:0.95±0.03]x8C
 Jacket: PVC NOUL 65P

P1	P2
1 WHITE	8
2 ORANGE	7
3 BLACK	6
4 RED	5
5 GREEN	4
6 YELLOW	3
7 BLUE	2
8 BROWN	1



Note:
 • Material: Housing-polycarbonate, clear
 Terminal-0.36[.014] thick phosphor bronze.
 Thick gold in localized gold plate.
 Area, Gold Flash over the remainder.
 Over 2.54mm[.000100] thick nickel underplate.

Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-8/8/W-5	A	1,525±20(5ft)	White	1,525-1,535mm
AT-S-26-8/8/W-7	B	2,135±30(7ft)	White	2,135-2,145mm
AT-S-26-8/8/W-10	C	3,050±60(10ft)	White	3,050-3,060mm
AT-S-26-8/8/W-12	D	3,660±60(12ft)	White	3,660-3,670mm
AT-S-26-8/8/W-14	E	4,270±60(14ft)	White	4,270-4,280mm
AT-S-26-8/8/W-25	F	7,625±100(25ft)	White	7,625-7,635mm
AT-S-26-8/8/W-50	G	15,250±150(50ft)	White	15,250-15,260mm



Scale	Free	Date	Name		
TOLERANCE		Drawn	08.07.13	Wilson	
X.	±X	Approved	08.07.13	Groll	
X.X	±X				
X.XX	±X				
DIM	TOL				
X.°	±X°				
X.X°	±X°				
Angle	TOL	Id.	Modification	Date	Name



Title	
Modular cable - Straight	
8P8C 50µm, 26AWG, White, 5-50 feet	
ASSMANN WSW-No.	
AT-S-26-8/8/W-xx	
Drawing-No.	
Replace	rev00
Sheet	1/1