

Technical specification :

| | |
|-------------------------------------|---------------------------|
| Rated voltage: IEC 61076-2-104 | 30 V |
| Current rating: IEC 61076-2-104 | 3 A at 40°C |
| Insulation resistance: IEC 60512 | ≥100 MΩ |
| Pollution degree: IEC 60664-1 | 3/2 |
| Degree of protection: IEC 60529 | IP 67, in mated condition |
| Temperature range: IEC 60664-1 | -30°C ... +80°C |
| Mating cycles: IEC 60512-9a | ≥100 |

Materials:

| | |
|------------------|----------------------|
| Contact: | CuZn |
| Contact plating: | Nickel, gold plated |
| Contact carrier: | TPU GF, UL 94 |
| Coupling screw: | GD-Zn, nickel plated |
| Moulding body: | TPU, UL 94, grey |

Installation specification:



| | |
|--------------------------|--|
| Recommended torque: | 0,4 Nm |
| Conec installation tool: | Torque wrench: 36-000200 Insert across flats 9: 36-000210 |

Contact assignment:

- 1 ■ brown
- 2 ■ white
- 3 ■ blue
- 4 ■ black

| Part no: | Description: | Length L: | Cable: |
|----------|---------------------------|-----------|--|
| 42-10060 | SAL - 8 - RSW4 - 2 / K1 | 2m | TPU, UL 20549, black, 4x0,25mm ² Cable: 781-K12400 |
| 42-10061 | SAL - 8 - RSW4 - 3 / K1 | 3m | |
| 42-10062 | SAL - 8 - RSW4 - 5 / K1 | 5m | |
| 42-10063 | SAL - 8 - RSW4 - 10 / K1 | 10m | |
| 42-xxxxx | SAL - 8 - RSW4 - ... / K1 | x | |

D see data sheet cable

| | | | | | | | | | | | | | |
|--|---|---|--|----------|---|-----------|--|------|------|-------|----------|-------|-------|
| DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant | Index: b 16.03.11 VF Ä3945 Coupling screw modified, spanner flats added, data sheet modified | |  dim. in mm | | title: Male connector M8x1 angled | | | | | | | | |
| | | | <table border="1"> <tr> <td></td> <td>date</td> <td>name</td> </tr> <tr> <td>drawn</td> <td>04.10.07</td> <td>Franz</td> </tr> <tr> <td>appd.</td> <td>04.10.07</td> <td>Mankopf</td> </tr> </table> | | | | | date | name | drawn | 04.10.07 | Franz | appd. |
| | | date | name | | | | | | | | | | |
| | drawn | 04.10.07 | Franz | | | | | | | | | | |
| | appd. | 04.10.07 | Mankopf | | | | | | | | | | |
| tolerance of cable: L ≤ 4m: L + 40mm L > 4m: L + 1% | | | | dwg no: | | | | | | | | | |
| general tolerance: 0 ± 0,50mm 0,0 ± 0,25mm 0,00 ± 0,10mm | |  | | 42K1A016 | | | | | | | | | |
| THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH | | | | part no: | | see table | | | | | | | |