



Scotchâ Tape 313

Low Noise Performance BOPP Box Sealing Tape

Temporary Data Sheet

Updated : Aug 2000

Supersedes : none

Product Description	# 313 is a box sealing tape with a polypropylene film backing and acrylic adhesive. The polypropylene backing is conformable,	provides edge tear and split resistance. The high coating weight of the acrylic adhesive makes it ideal for wide temperature swings and applications where it is applied.	It adheres well to recycled liner paper and will maintain its performance and appearance better than most products when exposed to UV light or fluorescent lighting.
----------------------------	--	--	--

Physical Properties

Not for specification purposes

Adhesive Type	Acrylic	
Backing	40 micron bi-axially oriented Polypropylene	
Total Thickness	65 micron (0.065mm)	AFERA 4006
Product Colours	Transparent, tan	
Available Widths Available Lengths	Contact your local sales office	
Core Size (ID)	3" (76mm)	
Storage Conditions	Store behind present stock, in a clean dry place. Temperature of 4-26°C (40-80 °F) and 40-50% Relative Humidity are recommended. Rotate your stock. Under correct storage conditions the tape maintains its characteristics for one year (shelf life).	

Performance Characteristics

Not for specification purposes

Adhesion to Stainless Steel	3.3 N/cm	AFERA 4001
Tensile Strength	61.3 N/cm	AFERA 4004
Elongation	165 %	AFERA 4005
Application	Best applied at room temperature onto a clean, dry, dust-free fibreboard surface. Once applied the product performs well on fibreboard boxes subjected to temperatures below 0°C (32°F)	

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



Packaging Systems Division

© 3M United Kingdom PLC 1999

3M ITALIA S.p.A.
Packaging Systems Customer Service
Via S. Bovio 3 - Milano S. Felice
20090 SEGRATE MI
ITALY

Tel. + 39 02 7035 3174/3173
Fax. + 39 02 7035 2104/3124