

THIS IS A CONTROLLED DOCUMENT.

APPLICATOR PARTS LIST				TYPE			AMP INCORPORATED HARRISBURG, PENNA.				
				ENDFEED			FLAG TAB				
NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	CRIMPING DATA	TERMINALS		
1	WIRE CRIMPER	1	456424-1	42				TO APPLY TERMINAL	42770		
2	INS. CRIMPER	1	810225	43				SPEC 114-2028	42771		
3	ANVIL	1	810219	44	HOLD DOWN	1	810499	WIRE SIZE	CRIMP HEIGHT		
4	ANVIL SPACER			45				18	.091		
5	SHEAR BLADE	1	810500	46				16	.096		
6	REAR SHEAR PLATE	1	810224	47				14	.103		
7	SHEAR BLADE SPACER LEFT	1	371984	48							
8	FRONT SHEAR PLATE			49							
9	SHEAR BLADE SPACER RIGHT	1	810226	50				CRIMP	SIZE	TYPE	FEED
10	FRONT ANVIL SPACER PLT.			51				WIRE	.130	"F"	
11	TOOL SPACER			52				INSUL.	.180	"O"	.500
12	CRIMP SPACER	1	370592	53				SLEEVED			
13	FRONT STRIP GUIDE	1	810222	54				INSULATION RANGE	WIRE RANGE		
14	REAR STRIP GUIDE	1	810221	55				.080-.160	18-14		
				56				EXPLODED VIEW			
15	RAM	1	471911	57				A-6000-18 A-6000-19			
16	TOOL HOLDER			58				REMARKS:			
17	ADJ. CRIMP MOUNT	1	465392-1	59							
18	ADJ. BLOCK			60							
19	APPLICATOR MOUNT ASSY.	1	1-471707-2	61							
20	BASE PLATE			62							
21	BASE BLOCK			63							
22	STRIP GUIDE PLATE			64							
23	ANVIL HOLDER			65	TENSION ADJ PLATE	1	374999				
24	AUX. ANVIL HOLDER				MISCELLANEOUS						
25	STRIPPER			66							
26	STRIPPED MOUNT			67							
27	RETAINER PLATE			68							
28	STRIPPER MOUNT BRACKET			69							
29	STRIPPER BUSHING			70							
30	STOCK DRAG	1	810223	71							
31	STOCK DRAG HANDLE	1	375382	72							
32	STOCK DRAG STUD	2	354045-1	REV.	REVISION RECORD	DATE	BY	ECN			
33	STOCK DRAG SPRING	2	1-23847-1	A	EC-A-238790	3/12/92	TA				
34	STOCK DRAG ADJ. SCREW			B	ECN A-395892	9-92	MS				
35	FEED FINGER HOLDER			C	ELR-06-006523	3-06	MS				
36	FEED FINGER	1	375093								
37	FEED FINGER TIP										
38	FEED FINGER SPACER										
39	BASE CASTING	1	570238								
40	GUARD	1	457668-7								
41											

CRIMPING DATA		TERMINALS
TO APPLY TERMINAL		42770
SPEC 114-2028		42771
WIRE SIZE	CRIMP HEIGHT	
18	.091	
16	.096	
14	.103	
CRIMP	SIZE	TYPE
WIRE	.130	"F"
INSUL.	.180	"O"
SLEEVED		.500
INSULATION RANGE	WIRE RANGE	
.080-.160	18-14	
EXPLODED VIEW		
A-6000-18 A-6000-19		
REMARKS:		
<p>■ DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT</p> <p>THIS APPLICATOR IS TO BE USED ON AMP-O-LECTRIC 1-471273-3</p>		
DIST.	4	
DESIGNED	K STAKEM	
SERIAL NO.	DATE SHIPPED	3-7-79
CUSTOMER NAME AND ADDRESS	ALIGN. GA. 679597-1	
APPLICATOR NUMBER	REV.	C 6722502
SHEET	1 OF 1	

THIS DRAWING IS UNPUBLISHED
 RELEASED FOR PUBLICATION
 BY AMP INCORPORATED
 ALL RIGHTS RESERVED
 COPYRIGHT 2000

DUPLICATE COPY - ORIGINAL LOST