



<p>POS. 1</p>  <p>2x SCREW 4-40 UNC with phillips head</p>	<p>POS. 2</p>  <p>1x CABLE STRAIN RELIEF</p>
<p>POS. 3</p>  <p>2x COVER SCREW</p>	<p>POS. 4</p>  <p>2x CABLE STRAIN RELIEF SCREW</p>

Directive 2002/95/EC  
RoHS  
Compliant

**NOTES:**

- HOOD: PBT GF UL 94 V0
- SCREW 4-40 UNC: STEEL; NICKEL PLATED
- SCREW FOR STRAIN RELIEF: STEEL; NICKEL PLATED
- COVER SCREW: STEEL; NICKEL PLATED
- STRAIN RELIEF: STEEL; NICKEL PLATED
- FEMALE CONNECTOR 7W2, CRIMP STYLE WITH WIRE BRIDGE AWG 22  
SIGNAL CONTACTS: COPPER ALLOY; 7,5A nominal  
PLATING: 30µm HARD GOLD over min. 50µm NICKEL  
FEMALE CONTACTS WIRE BRIDGE FROM POS. 1 TO POS. 2

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH			
DO NOT ALTER CAD DRAWING BY HAND			
rev.	description	date	name
a	Origin		

tolerance	ISO 2768-m
dim. in mm	
date	name
drawn	12.08.08 Schmidt
appd.	12.08.08 Kühle
norm	
d-old	
<b>CONEC</b>	

scale:	2:1	
material:	see notes	
title:		
PLASTIC HOOD, straight cable exit with 7W2 Female Crimp Connector with wire bridge		
dwg no:	Inventor 10	DIN-A3
	13K1A2569	sh: 1
part no:	13-000241	