

Specification Sheet

Part Number: 596-00242



Solar Label, Clear Laminate, UV Stable, 4.2" x 2.25", Acrylic, Clear, 50/roll

Article Number	596-00242
Type	LAM1
Color	Clear (CL)
Features & Benefits	<ul style="list-style-type: none">• Made with UV stable inks and materials for durability and weather resistance.• The labels are supplied with aggressive adhesive to ensure long life.• Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Quantity Per	roll

Product Description

HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, Clear Laminate, UV Stable, 4.2" x 2.25", Acrylic, Clear, 50/roll

Global Part Name

LAM1-V-CL

Technical Description

Clear Laminate Label, UV stable, 4.2" X 2.25", Clear

Local Order Number 2

Cross Reference = 10 per pack: 596-00670

Width W (Imperial)

4.2

Width W (Metric)

106.6

Thickness T (Metric)

64.0

Height H (Imperial)

2.25

Height H (Metric)

57.10

Material

Vinyl

Material Shortcut

V

Adhesive

Acrylic

Halogen free No

Adhesive Operating Temperature -40°F to +180°F (-40°C to +82°C)

Operating Temperature (Metric) -40°F to +174°F (-40°C to +79°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB IFC 2012 UL 969 NEC2011

Warranty (US) Yes

UL Recognized (US) Yes

Package Quantity(Imperial) 50

Package Quantity (Metric) 50

Customs Number 3919102055

Labels per Column 1

Labels per Row 1

Weight (Metric) 0.521

Weight (Imperial) 3.2

