


DETAIL INNER



RECOMMEND PCB Layout


REV ISIONS		DATE	BY	APP'D
A	FIRST VERSION		GF	SM
B	ADD PART No.		GF	SM

NOTES :

- 1. MATERIALS AND FINISH:
 - HOUSING: PA66
 - CONTACTS: COPPER ALLOY, FINISH: TIN OVER NICKEL UNDERPLATE
- 2. MUST COMPLY WITH DIRECTIVE 2002/95/EC (ROHS)
- 3. WIRE TYPES AND SIZES ACCEPTED
 WIRE RANGE: 14AWG~20AWG(SOLID&STRANDED)
 STRIP LENGTH: 7.5mm~8.5mm
- 4. PACKAGED IN TRAY.
- 5. CURRENT RATING: 6Amp AC300V.
- 6. OPERATION TEMPERATURE: -40°C TO +105°C

P/N: *-2834011-*

COLOR CODE:



- 1=GREEN 2=2 POSN
- 2=BLUE 3=3 POSN
- 3=BROWN 4=4 POSN
- 4=ORANGE 5=5 POSN
- 5=GREY 6=6 POSN
- 6=RED 7=7 POSN
- 7=YELLOW 8=8 POSN
- 8=PURPLE
- 9=WHITE
- 0=BLACK

REMARK: THE DIFFERENT COLORS COULD BE COMBINED TO THE NEW CONNECTOR P/NS FOR CUSTOMER REQUEST.

④	CONTACT
③	LEVER(orange)
②	COVER
①	HOUSING

29.5	8 POSN
26	7 POSN
22.5	6 POSN
19	5 POSN
15.5	4 POSN
12	3 POSN
8.5	2 POSN
A	NO. OF POSITIONS

THIS DRAWING IS A CONTROLLED DOCUMENT

DESIGNER	CHK	DATE
W. L.		

DATE	BY	APP'D
11-4-13/048		

35mm Top Entry Modular Screwless Conn.

SIZE 1 CODE 00779

SCALE 1:1

REV B