

System connectors - FLKM 50/4-FLK14/PA-S135 - 2288590

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




VARIOFACE front adapter, for Siemens SIMATIC® S5-135U, 4 x 8 channels can be connected

The illustration shows versions
FLKM 50-PA-S135/P and FLKM
50/4-FLK14/PA-S135



Key commercial data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 017918 057114 |
| Weight per Piece (excluding packing) | 255.8 GRM |
| Custom tariff number | 85369010 |
| Country of origin | Germany |

Technical data

General

| | |
|---------------------------------|--|
| Nominal voltage U_N | < 50 V AC |
| | 60 V DC |
| Max. permissible current | 0.5 A (per path) |
| | 8 A (per connection, supply via separate power supply) |
| Max. permissible total current | 3 A (per Byte, for supply via connector) |
| Channels which can be connected | 32 |
| Connection type, connector | Flat-ribbon cable connector in acc. with IEC 60603-13 |
| Number of connectors | 4 |
| No. of positions, connector | 14 |
| Number of positions | 50 |
| Mounting position | any |

System connectors - FLKM 50/4-FLK14/PA-S135 - 2288590

Technical data

General

| | |
|------------------------|-------------------------|
| Standards/regulations | IEC 60664 |
| | IEC 60664 A |
| | DIN VDE 0110 |
| | DIN VDE 0160 (in parts) |
| Pollution degree | 2 |
| Surge voltage category | II |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27250313 |
| eCl@ss 4.1 | 27250313 |
| eCl@ss 5.0 | 27250313 |
| eCl@ss 5.1 | 27250313 |
| eCl@ss 6.0 | 27242208 |
| eCl@ss 7.0 | 27242208 |
| eCl@ss 8.0 | 27242208 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001423 |
| ETIM 3.0 | EC001423 |
| ETIM 4.0 | EC001423 |
| ETIM 5.0 | EC002584 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211824 |
| UNSPSC 7.0901 | 39121421 |
| UNSPSC 11 | 39121421 |
| UNSPSC 12.01 | 39121421 |
| UNSPSC 13.2 | 39121421 |

Approvals

Approvals

System connectors - FLKM 50/4-FLK14/PA-S135 - 2288590

Approvals

Approvals

GOST

Ex Approvals

Approvals submitted

Approval details



Drawings

Circuit diagram

