



GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:
SEE DRAWING C01-8646-0000

TIN-LEAD PART-NUMBER

| SHELL | A±0.38 | B±0.12 | C±0.10 | D±0.25 | G±0.25 | PART NUMBER |
|-------|--------|--------|--------|--------|--------|--------------|
| 09 | 30.81 | 24.99 | 16.96 | 16.79 | 5.90 | D09P25K*PA00 |
| 15 | 39.14 | 33.32 | 25.18 | 25.12 | 5.90 | D15P25K*PA00 |
| 25 | 53.03 | 47.04 | 39.12 | 38.84 | 5.70 | D25P25K*PA00 |
| 37 | 69.32 | 63.50 | 55.68 | 55.30 | 5.70 | D37P25K*PA00 |

Plating: 4 ---> flash AU
Plating: 5 ---> 0.4» AU
Plating: 6 ---> 0.76» AU

LEAD-FREE PART-NUMBER

| SHELL | A±0.38 | B±0.12 | C±0.10 | D±0.25 | G±0.25 | PART NUMBER |
|-------|--------|--------|--------|--------|--------|----------------|
| 09 | 30.81 | 24.99 | 16.96 | 16.79 | 5.90 | D09P25K*PA00LF |
| 15 | 39.14 | 33.32 | 25.18 | 25.12 | 5.90 | D15P25K*PA00LF |
| 25 | 53.03 | 47.04 | 39.12 | 38.84 | 5.70 | D25P25K*PA00LF |
| 37 | 69.32 | 63.50 | 55.68 | 55.30 | 5.70 | D37P25K*PA00LF |

Plating: 4 ---> flash AU
Plating: 5 ---> 0.4» AU
Plating: 6 ---> 0.76» AU

European Views

| | | | | | | | |
|--------------------|------------|---------|----------|---------------------------------------|------------------|------------|---------|
| www.fciconnect.com | | surface | ISO 1302 | tolerance std | ISO 406 ISO 1101 | projection | mm |
| Dr JARRY | | ANGULAR | ✓ | TOLERANCES UNLESS OTHERWISE SPECIFIED | | A3 | Scale 2 |
| Eng PESSON | 1994-04-20 | LINEAR | | 0.X | ±0.1 | | |
| Chr NIRMAL GEORGE | 2009-11-24 | 0.XX | 0.XX | ±0.1 | ECN | 109-0268 | |
| Appr SUDHIR VARMA | 2009-11-24 | 0.XXX | 0.XXX | ±0.1 | D-SUB | Spec ref - | |

| rev | ecn no | dr | date |
|-----|-----------|-----|------------|
| C | - | SJO | 1997/09/05 |
| D | LS06-0074 | LGO | 2006/05/10 |
| E | LS06-0097 | LGO | 2006/07/29 |
| F | 109-0268 | NG | 2009-11-24 |

FCI MALE CONNECTOR
WIRE WRAP (3 LEVELS)
catalog no

Rev. F
C01-8646-0242
CUSTOMER sheet 1 of 1