

## Wire-wound Chip Inductors (LB series)[LB]

## LB3218T330M



## ■ Features

- Item Summary  
33uH±20%, 0.215A, 1207/3218 (EIA/JIS)
- Lifecycle Stage  
Mass Production
- Standard packaging quantity (minimum)  
Taping Embossed 2000pcs

## ■ Products characteristics table

Inductance	33 uH ± 20 %
Case Size (EIA/JIS)	1207/3218
Rated Current (max)	0.215 A
DC Resistance (max)	0.975 Ω
DC Resistance (typ)	0.75 Ω
LQ Measuring Frequency	2.52 MHz
Self Resonant Frequency (min)	15 MHz
Operating Temp. Range	-40 to +105 °C (Including-self-generated heat)
Temperature characteristic (Inductance change)	± 25 %
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

## ■ External Dimensions

Dimension L	3.2 ±0.2 mm
Dimension W	1.8 ±0.2 mm
Dimension T	1.8 ±0.2 mm
Dimension e	0.6 ±0.2 mm

2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.  
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.  
 Before making final selection, please check product specification.

Wire-wound Chip Inductors (LB series)

LB3218T330M



Dimension	unit : mm	unit : inch
Length :	3.2 +/- 0.2	( 0.126 +/- 0.008 )
Width :	1.8 +/- 0.2	( 0.071 +/- 0.008 )
Height :	1.8 +/- 0.2	( 0.071 +/- 0.008 )

Inductance :	33	uH	( test freq at 2.52MHz )
DC Resistance :	0.75 / 0.975	ohm	( typ / max )
Rated Current :	215	mA	

Rated current typical : 10% reduction from initial L value.  
and Temperature will rise by 20 deg C

