

## P/N: T911630ACC

### Copyright

© 2017, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

### Document identity

Publ. No.: T911630ACC

Release:

Commit: 41557

Language: en-US

Modified: 2017-03-23

Formatted: 2017-05-09

### Website

<http://www.flir.com>

### Customer support

<http://support.flir.com>

### Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to [exportquestions@flir.com](mailto:exportquestions@flir.com) with any questions.



<b>General description</b>	
Power supply, including multiple plugs, to charge the battery when it is inside the camera.	
<b>Power system</b>	
AC operation	100–240 VAC, 50/60 Hz, 5 VDC out
Power	3 A at 5 VDC
<b>Physical data</b>	
Size (L × W × H)	58 × 38 × 31 mm (2.3 × 1.5 × 1.2 in.)
Cable length	1.0 m (3.3 ft.)
<b>Shipping information</b>	
Packaging, type	Cardboard box
List of contents	<ul style="list-style-type: none"> <li>• Power supply including cable</li> <li>• EU plug</li> <li>• UK plug</li> <li>• US plug</li> <li>• AU plug</li> <li>• Korea plug</li> </ul>
Packaging, weight	180 g (0.40 lb.)
Packaging, size	110 × 70 × 63 mm (4.3 × 2.8 × 2.5 in.)
EAN-13	4743254003163
UPC-12	845188014568
Country of origin	Estonia

### Compatible with the following products

- 78502-0101; FLIR E75 24°
- 78504-0101; FLIR E75 24° + 14°
- 78506-0101; FLIR E75 24° + 14° & 42°
- 78505-0101; FLIR E75 24° + 42°
- 78503-0101; FLIR E75 42°
- 78507-0101; FLIR E75 42° + 14°
- 78502-0201; FLIR E85 24°
- 78504-0201; FLIR E85 24° + 14°
- 78506-0201; FLIR E85 24° + 14° & 42°



## Power supply, 15 W/3 A

---

**P/N: T911630ACC**

© 2017, FLIR Systems, Inc.

#T911630ACC; r. /41557; en-US

- 78505-0201; FLIR E85 24° + 42°
- 78503-0201; FLIR E85 42°
- 78507-0201; FLIR E85 42° + 14°
- 78502-0301; FLIR E95 24°
- 78504-0301; FLIR E95 24° + 14°
- 78506-0301; FLIR E95 24° + 14° & 42°
- 78505-0301; FLIR E95 24° + 42°
- 78503-0301; FLIR E95 42°
- 79302-0101; FLIR T530 24°
- 79306-0101; FLIR T530 24° + 14° & 42°
- 79305-0101; FLIR T530 24° + 42°
- 79304-0101; FLIR T530 24° + 14°
- 79303-0101; FLIR T530 42°
- 79307-0101; FLIR T530 42° + 14°
- 79302-0201; FLIR T540 24°
- 79304-0201; FLIR T540 24° + 14°
- 79306-0201; FLIR T540 24° + 14° & 42°
- 79305-0201; FLIR T540 24° + 42°
- 79303-0201; FLIR T540 42°
- 79307-0201; FLIR T540 42° + 14°