



RECOMMENDED PC BOARD PAD PATTERN  
0.20 [.008] THICK STENCIL

- |   |   |
|---|---|
| <p>1 HOUSING: GLASS FILLED, FLAME RETARDANT POLYESTER, BLACK CONTACTS: PHOSPHOR BRONZE. VACUUM COVER: STAINLESS STEEL.</p> <p>2 CONTACTS: DUPLEX PLATED: 0.76μm [.000030] GOLD IN CONTACT AREA 3.81-7.62μm [.000150-.000300] BRIGHT TIN-LEAD ON LEADS, ALL OVER 1.27μm [.000050] MINIMUM NICKEL.</p> <p>3 THESE DIMENSIONS PERTAIN TO CAVITY CENTERLINES ONLY. NOT TO CONTACT LOCATION</p> <p>4 POINT OF MEASUREMENT FOR PLATING THICKNESS.</p> <p>5 POINT OF CONTACT DIMENSION.</p> <p>6 MARK PART NUMBER AND DATE CODE IN APPROXIMATE LOCATION SHOWN, EITHER SIDE.</p> <p>7 TOLERANCE IS NON-CUMULATIVE.</p> <p>8 5.2 [.205] MIN TARGET AREA FOR VACUUM PICK-UP COVERS TO BE REMOVED AFTER SOLDERING.</p> | <p>9 FOR 2 POS, DATE CODE IS STAMPED OPPOSITE SIDE OF TE LOGO.</p> <p>10 TE LOGO AND CSA LOGO ARE MOLDED INTO HOUSING.</p> <p>11 NO PART NUMBER MARKING REQUIRED ON THIS PART.</p> <p>12 CONTACT: DUPLEX PLATED: 0.76 MICROMETERS (.000030) GOLD IN CONTACT AREA, 3.81-7.62 MICROMETERS (.000150-.000300) MATTE TIN ON LEADS, ALL OVER 1.27 MICROMETERS (.000050) MINIMUM NICKEL.</p> <p>13 ROHS 2002/95/EC COMPLIANT</p> |
|---|---|

2	99.06 [3.900]	101.6 [4.000]	40	3-147738-9
2	96.52 [3.800]	99.06 [3.900]	39	3-147738-8
2	93.98 [3.700]	96.52 [3.800]	38	3-147738-7
2	91.44 [3.600]	93.98 [3.700]	37	3-147738-6
2	88.90 [3.500]	91.44 [3.600]	36	3-147738-5
2	86.34 [3.400]	88.90 [3.500]	35	3-147738-4
2	83.82 [3.300]	86.34 [3.400]	34	3-147738-3
2	81.28 [3.200]	83.82 [3.300]	33	3-147738-2
2	78.74 [3.100]	81.28 [3.200]	32	3-147738-1
2	76.20 [3.000]	78.74 [3.100]	31	3-147738-0
2	73.66 [2.900]	76.20 [3.000]	30	2-147738-9
2	71.12 [2.800]	73.66 [2.900]	29	2-147738-8
2	68.58 [2.700]	71.12 [2.800]	28	2-147738-7
2	66.04 [2.600]	68.58 [2.700]	27	2-147738-6
2	63.5 [2.500]	66.04 [2.600]	26	2-147738-5
2	60.96 [2.400]	63.5 [2.500]	25	2-147738-4
2	58.42 [2.300]	60.96 [2.400]	24	2-147738-3
2	55.88 [2.200]	58.42 [2.300]	23	2-147738-2
2	53.34 [2.100]	55.88 [2.200]	22	2-147738-1
2	50.8 [2.000]	53.34 [2.100]	21	2-147738-0
2	48.26 [1.900]	50.8 [2.000]	20	1-147738-9
2	45.72 [1.800]	48.26 [1.900]	19	1-147738-8
2	43.18 [1.700]	45.72 [1.800]	18	1-147738-7
2	40.64 [1.600]	43.18 [1.700]	17	1-147738-6
2	38.1 [1.500]	40.64 [1.600]	16	1-147738-5
2	35.56 [1.400]	38.1 [1.500]	15	1-147738-4
2	33.02 [1.300]	35.56 [1.400]	14	1-147738-3
2	30.48 [1.200]	33.02 [1.300]	13	1-147738-2
2	27.94 [1.100]	30.48 [1.200]	12	1-147738-1
2	25.4 [1.000]	27.94 [1.100]	11	1-147738-0
2	22.86 [.900]	25.4 [1.000]	10	147738-9
2	20.32 [.800]	22.86 [.900]	9	147738-8
2	17.78 [.700]	20.32 [.800]	8	147738-7
2	15.24 [.600]	17.78 [.700]	7	147738-6
2	12.7 [.500]	15.24 [.600]	6	147738-5
2	10.16 [.400]	12.7 [.500]	5	147738-4
2	7.62 [.300]	10.16 [.400]	4	147738-3
2	5.08 [.200]	7.62 [.300]	3	147738-2
2	2.54 [.100]	5.08 [.200]	2	147738-1

11 9 OBSOLETE

FINISH	B	A	NO OF POSN	PART NUMBER
THIS DRAWING IS A CONTROLLED DOCUMENT.				
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPROVED: J. OLSON
0 PLC ± -		1 PLC ± -		DATE: 19JAN01
1 PLC ± -		2 PLC ± -		BY: R. BROWN
2 PLC ± -		3 PLC ± .005		CHK: J. OLSON
3 PLC ± -		4 PLC ± -		DATE: 19JAN01
4 PLC ± -		ANGLES ± -		NAME: J. OLSON
MATERIAL: Δ		FINISH: ΔΔ		PRODUCT SPEC: 108-25026
WEIGHT: -		SIZE: A1		APPLICATION SPEC: 114-25018
CUSTOMER DRAWING		SCALE: 6:1		RESTRICTED TO: -
SHEET 1 OF 2		REV: H5		RECT. ASSY., MOD IV, SINGLE ROW, .100 CL, SURFACE MOUNT, VERTICAL, DUAL ENTRY CLOSED ENTRY

△	99.06	[3.900]	101.6	[4.000]	40	△	8-147738-9
△	96.52	[3.800]	99.06	[3.900]	39	△	8-147738-8
△	93.98	[3.700]	96.52	[3.800]	38	△	8-147738-7
△	91.44	[3.600]	93.98	[3.700]	37	△	8-147738-6
△	88.90	[3.500]	91.44	[3.600]	36	△	8-147738-5
△	86.34	[3.400]	88.90	[3.500]	35	△	8-147738-4
△	83.82	[3.300]	86.34	[3.400]	34	△	8-147738-3
△	81.28	[3.200]	83.82	[3.300]	33	△	8-147738-2
△	78.74	[3.100]	81.28	[3.200]	32	△	8-147738-1
△	76.20	[3.000]	78.74	[3.100]	31	△	8-147738-0
△	73.66	[2.900]	76.20	[3.000]	30	△	7-147738-9
△	71.12	[2.800]	73.66	[2.900]	29	△	7-147738-8
△	68.58	[2.700]	71.12	[2.800]	28	△	7-147738-7
△	66.04	[2.600]	68.58	[2.700]	27	△	7-147738-6
△	63.5	[2.500]	66.04	[2.600]	26	△	7-147738-5
△	60.96	[2.400]	63.5	[2.500]	25	△	7-147738-4
△	58.42	[2.300]	60.96	[2.400]	24	△	7-147738-3
△	55.88	[2.200]	58.42	[2.300]	23	△	7-147738-2
△	53.34	[2.100]	55.88	[2.200]	22	△	7-147738-1
△	50.8	[2.000]	53.34	[2.100]	21	△	7-147738-0
△	48.26	[1.900]	50.8	[2.000]	20	△	6-147738-9
△	45.72	[1.800]	48.26	[1.900]	19	△	6-147738-8
△	43.18	[1.700]	45.72	[1.800]	18	△	6-147738-7
△	40.64	[1.600]	43.18	[1.700]	17	△	6-147738-6
△	38.1	[1.500]	40.64	[1.600]	16	△	6-147738-5
△	35.56	[1.400]	38.1	[1.500]	15	△	6-147738-4
△	33.02	[1.300]	35.56	[1.400]	14	△	6-147738-3
△	30.48	[1.200]	33.02	[1.300]	13	△	6-147738-2
△	27.94	[1.100]	30.48	[1.200]	12	△	6-147738-1
△	25.4	[1.000]	27.94	[1.100]	11	△	6-147738-0
△	22.86	[.900]	25.4	[1.000]	10	△	5-147738-9
△	20.32	[.800]	22.86	[.900]	9	△	5-147738-8
△	17.78	[.700]	20.32	[.800]	8	△	5-147738-7
△	15.24	[.600]	17.78	[.700]	7	△	5-147738-6
△	12.7	[.500]	15.24	[.600]	6	△	5-147738-5
△	10.16	[.400]	12.7	[.500]	5	△	5-147738-4
△	7.62	[.300]	10.16	[.400]	4	△	5-147738-3
△	5.08	[.200]	7.62	[.300]	3	△	5-147738-2
△	2.54	[.100]	5.08	[.200]	2	△	5-147738-1

11 9 OBSOLETE

FINISH	B	A	NO OF POSN	PART NUMBER
THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN R BROWN 19JAN01	APVD J OLSON 19JAN01	
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		
0 PLC ± -		1 PLC ± -		
1 PLC ± -		2 PLC ± -		
2 PLC ± -		3 PLC ± .005		
3 PLC ± -		4 PLC ± -		
4 PLC ± -		ANGLES ± -		
MATERIAL	FINISH	WEIGHT	SIZE	SCALE
△	△	-	A1	6:1
CUSTOMER DRAWING		00779	147738	SHEET 2 OF 2