

XDS560v2 LC Traveler JTAG Emulator



Documentation

Installation Guide
[Drivers and Support](#)

Application

Debug hardware
 Debug software
 Flash programming

Warranty

1 year from date of purchase



Part #: 702597

XDS560v2 LC Traveler JTAG Emulator

Hardware Features

- Supports Texas Instruments Digital Signal Processors and Microcontrollers with **JTAG** interface:
 - C64x+ ● ARM
 - C28xxx ● OMAP3
 - C5000 ● OMAP4
 - C6000 ● OMAPL13x
 - DaVinci
- Advanced emulation controller provides high performance.
- Supports Embedded Trace Buffer (ETB) on selected TI devices
- USB 2.0 communications to host PC.
- Supports +1.2V to +4.1V

Software Features

- Compatible with Code Composer Studio™ Version 4.2 and later from Texas Instruments.
- Compatible with Texas Instruments Code Composer Studio™, and DSP BIOS
- Supports UniFlash™ programming utility from Texas Instruments
- Supports CCS DSS Java Scripting
- Compatible with Windows XP, Vista, Win7, and Linux Operating Systems

What's Included

- XDS560v2 LC Traveler JTAG Emulator with 20pin CTI JTAG cable.
- 20pin CTI JTAG to 14pin JTAG adapter.
- USB cable
- Quick Start Guide
- Technical Reference
- Warranty registration card
- CD-ROM with Emulation Drivers and Evaluation Version of Code Composer Studio™ (License Required)

You May Need

- Code Composer Studio™
- DSP Target Board (EVM, eZdsp™, DSK)

JTAG interfaces.

- 1 power LED
- 6 LEDs for operational status
- User accessible RESET switch
- USB Bus Powered. No external power supply required.
- RoHS Compliant

- Additional JTAG Adapters