

# HDSP-G01x, HDSP-G03x

10.16 mm (0.4 inch) Dual Digit General Purpose  
Seven-Segment Display



## Data Sheet



### Description

This 10.16 mm (0.4 inch) LED dual digit seven-segment display uses industry standard size package and pinout. The device is available in either common anode or common cathode. The choice of colors includes High Efficiency Red (HER), Green, AlGaAs Red, and Yellow. The gray face displays are suitable for indoor use.

### Applications

- Suitable for indoor use
- Not recommended for industrial application, i.e., operating temperature requirements exceeding +85°C or below -25°C<sup>[1]</sup>
- Extreme temperature cycling not recommended

Note:

1. For additional details, please contact your local Avago sales office or an authorized distributor.

### Features


- Industry standard size
- Industry standard pinout  
10.16 mm (0.4 inch)  
DIP lead on 2.54 mm
- Choice of colors  
High Efficiency Red (HER), Green, AlGaAs Red and Yellow
- Excellent appearance  
Evenly lighted segments gray package gives optimum contrast  
± 50° viewing angle
- Design flexibility  
Common anode or common cathode
- Categorized for luminous intensity  
Green and yellow categorized for color

### Devices

HER	Green	AlGaAs Red	Yellow	Description
HDSP-G01E	HDSP-G01G	HDSP-G01A	HDSP-G01Y	Common Anode
HDSP-G03E	HDSP-G03G	HDSP-G03A	HDSP-G03Y	Common Cathode

## Part Numbering System

5082 - X X X X-X X X X X  
 HDSP-X X X X-X X X X X




Notes:


1. For codes not listed in the figure above, please refer to the respective datasheet or contact your nearest Avago representative for details.
2. Bin options refer to shippable bins for a part number. Color and Intensity Bins are typically restricted to 1 bin per tube (exceptions may apply). Please refer to respective datasheet for specific bin limit information.

# Package Dimensions


FRONT VIEW




SIDE VIEW




TOP END VIEW



DIG.1



DIG.2




NOTE: DECIMAL POINTS WILL NOT BE LIGHTED UP

DIMENSIONS ARE IN MILLIMETERS (INCHES).

# Internal Circuit Diagram


## COMMON ANODE



### HDSP-G01E/G01G/G01Y/G01A

PIN No.	CONNECTION
1	CATHODE C (DIGIT 1)
2	CATHODE E (DIGIT 1)
3	CATHODE D (DIGIT 1)
4	COMMON ANODE (DIGIT 1)
5	COMMON ANODE (DIGIT 2)
6	CATHODE D (DIGIT 2)
7	CATHODE E (DIGIT 2)
8	CATHODE C (DIGIT 2)
9	CATHODE G (DIGIT 2)
10	CATHODE A (DIGIT 2)
11	CATHODE F (DIGIT 2)
12	CATHODE B (DIGIT 2)
13	CATHODE B (DIGIT 1)
14	CATHODE F (DIGIT 1)
15	CATHODE A (DIGIT 1)
16	CATHODE G (DIGIT 1)

## COMMON CATHODE



### HDSP-G03E/G03G/G03Y/G03A

PIN No.	CONNECTION
1	ANODE C (DIGIT 1)
2	ANODE E (DIGIT 1)
3	ANODE D (DIGIT 1)
4	COMMON CATHODE (DIGIT 1)
5	COMMON CATHODE (DIGIT 2)
6	ANODE D (DIGIT 2)
7	ANODE E (DIGIT 2)
8	ANODE C (DIGIT 2)
9	ANODE G (DIGIT 2)
10	ANODE A (DIGIT 2)
11	ANODE F (DIGIT 2)
12	ANODE B (DIGIT 2)
13	ANODE B (DIGIT 1)
14	ANODE F (DIGIT 1)
15	ANODE A (DIGIT 1)
16	ANODE G (DIGIT 1)

### Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Description	HER HDSP-G0xE	Green HDSP-G0xG	AlGaAs Red HDSP-G0xA	Yellow HDSP-G0xY	Units
Power Dissipation Segment	65	65	30	52	mW
Forward Current Segment	25 <sup>[1]</sup>	25 <sup>[2]</sup>	15 <sup>[3]</sup>	20 <sup>[4]</sup>	mA
Peak Forward Current per Segment (1/10 Duty Factor at 10 KHz)	100	100	80	80	mA
Operating Temperature Range	-35 to +85	-35 to +85	-35 to +85	-35 to +85	$^\circ\text{C}$
Storage Temperature Range	-35 to +85	-35 to +85	-35 to +85	-35 to +85	$^\circ\text{C}$
Reverse Voltage per Segment or DP	5	5	5	5	V
Wave Soldering Temperature for 3 seconds (at 2 mm Distance from the Body)	250	250	250	250	$^\circ\text{C}$

Notes:

1. Derate above  $25^\circ\text{C}$  at  $0.33\text{ mA}/^\circ\text{C}$ .
2. Derate above  $25^\circ\text{C}$  at  $0.33\text{ mA}/^\circ\text{C}$ .
3. Derate above  $25^\circ\text{C}$  at  $0.2\text{ mA}/^\circ\text{C}$ .
4. Derate above  $25^\circ\text{C}$  at  $0.27\text{ mA}/^\circ\text{C}$ .

### Electrical/Optical Characteristics at $T_A = 25^\circ\text{C}$

#### High Efficiency Red (HER)

Device HDSP-	Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
G01E G03E	Luminous Intensity/Segment	$I_V$		1.19		mcd	$I_F = 5\text{ mA}$
			1.25	2.60		mcd	$I_F = 10\text{ mA}$
	Forward Voltage	$V_F$		2.05	2.40	V	$I_F = 20\text{ mA}$
	Peak Wavelength	$\lambda_{\text{PEAK}}$		635		nm	
	Dominant Wavelength	$\lambda_d$		620		nm	
	Reverse Voltage	$V_R$	5			V	$I_R = 100\ \mu\text{A}$

#### Green

Device HDSP-	Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
G01G G03G	Luminous Intensity/Segment	$I_V$		3.20		mcd	$I_F = 10\text{ mA}$
			1.25	2.25	2.60	V	$I_F = 20\text{ mA}$
	Forward Voltage	$V_F$		2.05		V	$I_F = 10\text{ mA}$
	Peak Wavelength	$\lambda_{\text{PEAK}}$		568		nm	
	Dominant Wavelength	$\lambda_d$		573		nm	
	Reverse Voltage	$V_R$	5			V	$I_R = 100\ \mu\text{A}$

## AlGaAs Red

Device HDSP-	Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
G01A G03A	Luminous Intensity/Segment	I <sub>V</sub>		3.66		mcd	I <sub>F</sub> = 5 mA
			3.20	6.50		mcd	I <sub>F</sub> = 10 mA
	Forward Voltage	V <sub>F</sub>		1.85	2.00	V	I <sub>F</sub> = 20 mA
	Peak Wavelength	λ <sub>PEAK</sub>		660		nm	
	Dominant Wavelength	λ <sub>d</sub>		643		nm	
	Reverse Voltage	V <sub>R</sub>	5			V	I <sub>R</sub> = 100 μA

## Yellow

Device HDSP-	Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
G01Y G03Y	Luminous Intensity/Segment	I <sub>V</sub>		0.77		mcd	I <sub>F</sub> = 5 mA
			0.80	1.50		mcd	I <sub>F</sub> = 10 mA
	Forward Voltage	V <sub>F</sub>		2.15	2.60	V	I <sub>F</sub> = 20 mA
	Peak Wavelength	λ <sub>PEAK</sub>		595		nm	
	Dominant Wavelength	λ <sub>d</sub>		590		nm	
	Reverse Voltage	V <sub>R</sub>	5			V	I <sub>R</sub> = 100 μA

## Intensity Bin Limits (mcd at 10 mA)

Bin Name	HER/Green		Yellow		AlGaAs Red	
	Min. <sup>[1]</sup>	Max. <sup>[1]</sup>	Min. <sup>[1]</sup>	Max. <sup>[1]</sup>	Min. <sup>[1]</sup>	Max. <sup>[1]</sup>
G	NA	NA	0.801	1.250	NA	NA
H	1.251	2.000	1.251	2.000	NA	NA
I	2.001	3.200	2.001	3.200	NA	NA
J	3.201	5.050	NA	NA	3.201	5.050
K	NA	NA	NA	NA	5.051	8.000
L	NA	NA	NA	NA	8.001	12.650

Note:

1. Tolerance for each bin limit is ± 10%.

## Color Bin Limits (nm at 10 mA)

Color	Bin	Dominant Wavelength (nm)	
		Min. <sup>[1]</sup>	Max. <sup>[1]</sup>
Green	3	569.1	571.0
	4	571.1	573.0
	5	573.1	575.0
Yellow	1	585.5	588.5
	2	588.5	591.5
	3	591.5	594.5

Note:

1. Tolerance for each bin limit is 1 nm.

## High Efficiency Red (HER)




Figure 1. Maximum allowable average or DC current vs. ambient temperature.




Figure 2. Forward current vs. forward voltage.




Figure 3. Relative luminous intensity vs. DC forward current.




Figure 4. Relative efficiency (luminous intensity per unit current) vs. peak current.

## Green




Figure 5. Maximum allowable average or DC current vs. ambient temperature.




Figure 6. Forward current vs. forward voltage.




Figure 7. Relative luminous intensity vs. DC forward current.




Figure 8. Relative efficiency (luminous intensity per unit current) vs. peak current.



## AlGaAs Red




Figure 9. Maximum allowable average or DC current vs. ambient temperature.




Figure 10. Forward current vs. forward voltage.




Figure 11. Relative luminous intensity vs. DC forward current.




Figure 12. Relative efficiency (luminous intensity per unit current) vs. peak current.

## Yellow




Figure 13. Maximum allowable average or DC current vs. ambient temperature.




Figure 14. Forward current vs. forward voltage.




Figure 15. Relative luminous intensity vs. DC forward current.




Figure 16. Relative efficiency (luminous intensity per unit current) vs. peak current.

For product information and a complete list of distributors, please go to our web site: [www.avagotech.com](http://www.avagotech.com)

Avago, Avago Technologies, and the A logo are trademarks of Avago Technologies in the United States and other countries. Data subject to change. Copyright © 2005-2012 Avago Technologies. All rights reserved. Obsoletes 5989-3314EN AV02-3641EN - June 20, 2012

**AVAGO**  
TECHNOLOGIES