Embedded Artists

About Us	Products	Services	Support	Projects	Web Shop

Products

> Board Comparison Chart

» Developer's Kits

» OEM Boards

» QuickStart Boards

» Education Boards

↓ LPCXpresso & mbed

> LPCXpresso LPC1114

> LPCXpresso LPC11U14

> LPCXpresso LPC11C24

> LPCXpresso LPC1227

> LPCXpresso LPC1343

> LPCXpresso LPC1769

> LPCXpresso Prototype

> LPCXpresso Base

> LPCXpresso Value Pack

> LPCXpresso Motor Control

> mbed

» Displays

» Tools

» Accessories

LPC11U14 LPCXpresso Board

Picture not showing correct version of LPCXpresso board.

The LPC11U14 LPCXpresso board with NXP's ARM Cortex-M0 microcontroller has been designed to make it as easy as possible to get started with Cortex-M0. The LPCXpresso comprises a target board combined with a JTAG debugger. A free Eclipse-based IDE from Code Red is also included.

The LPC11U14 has 6 kB SRAM, 32 kB Flash, USB 2.0 Full-Speed Device, SSP, I2C, UART, ADC, etc. Embedded Artists also provides a Prototype board and a Base board that makes it possible to make experiments and prototyping with many peripherals.

Discount
Embedded Artists and Code Red offer LPCXpresso customers valuable discounts. Embedded Artists gives **15 EUR** discount on the regular Developer's kits and **7 EUR** off the LPCXpresso Base board. Code Red has an offer to upgrade to full-blown suites. For more information see LPCXpresso discount.

Price Information

EUR

Art.no: **EA-XPR-007** Buy

Currently out-of-stock

**Expected delivery date:
2011-07-30**

Price Information

EUR

LPCXpresso Kit containing LPC11U14 and Base Board

Art.no: **EA-XPR-107** Buy

Currently out-of-stock

**Expected delivery date:
2011-07-30**

Overview	**Specification**	MCU	Related Products	Resources	FAQ

LPC11U14 LPCXpresso Board

Processor	NXP's Cortex-M0 LPC11U14 microcontroller in LQFP48 package
Flash	32 kB
Data Memory	6 kB
Clock Crystals	12.000 MHz crystal for CPU
Dimensions	35 x 140 mm
Power	3.15V-3.3V external powering, or from USB via JTAG probe (LPC-LINK)
Connectors	• mini-B USB connector for LPC11U14 USB interface • All LPC11U14 pins available on expansion connector (2x27 pin rows, 100 mil pitch, 900 mil between rows)
Other	• Embedded JTAG (LPC-LINK) functionality via LPCXpresso toolchain • LPC-LINK can be connected to external target processor after modifications to the LPCXpresso board • LED on PIO0_7