

## Specification Sheet

Part Number: TAGPP2-788C

**HellermannTyton** Laser Tag Label, .66" x .31", 360 Per Sheet, PET, Clear, 1000/pkg

<b>Article Number</b>	594-00002
<b>Type</b>	TAGPP2
<b>Color</b>	Clear (CL)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• LaserTags are sheet fed for easy loading and fast printing.</li><li>• LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.</li><li>• LaserTags are printable using toner for long term UV exposure.</li><li>• LaserTags come in a variety of label sizes and types to fit most applications.</li></ul>
<b>Quantity Per</b>	pack

### Product Description

LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

<b>Short Description</b>	Laser Tag Label, .66" x .31", 360 Per Sheet, PET, Clear, 1000/pkg
<b>Global Part Name</b>	TAGPP2-788C-CL
<b>Width W (Imperial)</b>	0.66
<b>Width W (Metric)</b>	16.7
<b>Thickness T (Metric)</b>	64.0
<b>Height H (Imperial)</b>	0.33
<b>Height H (Metric)</b>	8.38
<b>Material</b>	Type 788C, Polyester, clear (CL)
<b>Material Shortcut</b>	788C
<b>Adhesive</b>	Acrylic
<b>Halogen free</b>	No
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature (Metric)</b>	-40°F to +199°F (-40°C to +93°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes

<b>Package Quantity(Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3919905060
<b>Labels per Column</b>	30
<b>Labels per Row</b>	12
<b>Weight (Metric)</b>	0.521
<b>Weight (Imperial)</b>	1.14