

# 96PR-102-UW2-M

## 203 dpi Mobile Barcode Printer, 2", 4 ips, USB/Wi-Fi



### Features

- 2" mobile barcode receipt printer
- Resolution: 203 dpi
- Max. print speed: 102mm (4")/sec
- USB, Wi-Fi
- 128 MB Flash memory and 64 MB SDRAM memory

### Specifications

<b>Resolution</b>	8 dots/mm (203 dpi)	
<b>Printing method</b>	Direct Thermal	
<b>Max. print speed</b>	102 mm (4")/second	
<b>Max. print width</b>	48 mm (1.89")	
<b>Max. print length</b>	2,286 mm (90")	
<b>Enclosure</b>	Plastic	
<b>Physical dimension (W x H x D)</b>	89.3 x 134.5 x 56.5 mm (3.52" x 5.3" x 2.22")	
<b>Weight (including battery)</b>	0.35 kg (0.77 lbs)	
<b>Drop specification</b>	1.5 m (5 ft), with IP54 case can be 1.5 m (5 ft)	
<b>IP rating</b>	IP42 (without case) IP54 (with case)	
<b>Max. roll capacity</b>	50 mm (2") OD	
<b>Processor</b>	32-bit RISC CPU	
<b>Memory</b>	<ul style="list-style-type: none"> <li>• 128 MB Flash memory</li> <li>• 64 MB SDRAM</li> </ul>	
<b>Interface</b>	<ul style="list-style-type: none"> <li>• USB 2.0</li> <li>• Bluetooth 4.0 (option)</li> <li>• NFC (option)</li> </ul>	<ul style="list-style-type: none"> <li>• 802.11 a/b/g/n Wireless</li> <li>• Bluetooth 4.2 + MFi (option)</li> <li>• RS-232 (option)</li> </ul>
<b>Power</b>	Two-cell, 7.4V <sub>DC</sub> , 1620 mAh Li-ion rechargeable battery	
<b>Operation switch, button</b>	<ul style="list-style-type: none"> <li>• 3 buttons (On/off, feed, and cover-open)</li> <li>• 2 color LED for printer status, 3 LEDs for battery status</li> </ul>	
<b>Sensors</b>	<ul style="list-style-type: none"> <li>• Reflective sensor</li> <li>• Head open sensor</li> </ul>	
<b>Internal fonts</b>	<ul style="list-style-type: none"> <li>• 8 alpha-numeric bitmap fonts</li> <li>• One Monotype Imaging® CG Triumvirate Bold Condensed scalable font</li> </ul>	
<b>Bar code</b>	<ul style="list-style-type: none"> <li>• 1D bar code Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 Data bar</li> <li>• 2D bar code PDF-417, Maxicode, DataMatrix, QR code, Aztec</li> </ul>	
<b>Printer language</b>	TSPL-EZ™ (EPL2, ZPL2), ESC-POS or CPCL emulation	
<b>Media type</b>	Receipt paper, Blaine receipt paper (Black mark in printing side) & Selected label	
<b>Media width</b>	Max 58 mm (2.28") *with adapter: 50.8 mm (2") and 25.4 mm (1") (user option)	
<b>Media thickness</b>	Receipt: 0.05 - 0.10 mm (2 - 4 mil) Label: Fasson standard label media up to 0.14 mm (5.5 mil)	
<b>Media height</b>	Label: Min. 25.4 mm (1")	
<b>Environment condition</b>	Operation: -20 - 50 °C (-4 - 122 °F), 10 - 90% non-condensing Storage: -30 - 70 °C (-22 - 158 °F), 10 - 90% non-condensing	
<b>Safety regulation</b>	FCC, IC, CE, CB, CCC, SRRC, BC, TUV, NCC, Energy Star®	
<b>Environmental concern</b>	Comply with RoHS, WEEE, REACH	
<b>Accessories</b>	<ul style="list-style-type: none"> <li>• Quick Start Guide</li> <li>• Li-ion battery</li> </ul>	<ul style="list-style-type: none"> <li>• Belt clip</li> <li>• Power adapter</li> </ul>
<b>Options</b>	<ul style="list-style-type: none"> <li>• 802.11 a/b/g/n Wireless network (supports either WiFi or Bluetooth)</li> <li>• MFi</li> <li>• NFC</li> <li>• Mini type USB 2.0</li> <li>• Li-ion battery</li> <li>• Charge station 4 cell (with changeable power connector)</li> <li>• IP54-rated environmental case with shoulder strap</li> <li>• Adapters for 1" or 2" media roll width</li> </ul>	<ul style="list-style-type: none"> <li>• Bluetooth</li> <li>• Linerless</li> <li>• Fork truck mount, cart mount</li> <li>• USB to RS-232 converter cable</li> <li>• Charge station 1 cell (with changeable power connector)</li> <li>• Vehicle power adapter</li> <li>• 12-24V<sub>DC</sub> automobile cigarette lighter plug</li> </ul>

### Ordering Information

Part Number	Description
96PR-102-UW2-M	Mobile Barcode Printer, 203dpi, 2", 4 ips, USB/Wi-Fi, US power cord
96PR-102-UW2-M-E	Mobile Barcode Printer, 203dpi, 2", 4 ips, USB/Wi-Fi, EU power cord