


**SRSL 4-T15**



tightening torque/thread      1.0 Nm/M 3      Inspection Test Pattern Size      A 4

Type      Cat.-No.      Qty.p.pck.  
**SRSL 4-T15**      41064.2      green/yellow      100


**Ratings:**

**Dimensions**      TS 15  
LxBxH (mm)      32x7x32  
Stripped Length      9 mm

**Max Rated Cross Section**

Single Wire (solid)      0.2-4 mm<sup>2</sup>  
Stranded Wire (flexible)      0.2-4 mm<sup>2</sup>  
Wire Size      AWG 22-10

**SRSLN 2.5-T32**



tightening torque/thread      0.7 Nm/M 2.5      Inspection Test Pattern Size      A 3

Type      Cat.-No.      Qty.p.pck.  
**SRSLN 2.5-T32**      41057.2      green/yellow      100

**Ratings:**

**Dimensions**      TS 32  
LxBxH (mm)      44x6x43  
Stripped Length      10 mm

**Max Rated Cross Section**

Single Wire (solid)      0.2-4 mm<sup>2</sup>  
Stranded Wire (flexible)      0.2-2.5 mm<sup>2</sup>  
Wire Size      AWG 22-14

**EARTH TERMINAL BLOCKS**

**SRSLN 2.5-T35**



tightening torque/thread      0.7 Nm/M 2.5      Inspection Test Pattern Size      A 3

Type      Cat.-No.      Qty.p.pck.  
**SRSLN 2.5-T35**      41058.2      green/yellow      100


**Ratings:**

**Dimensions**      TS 35  
LxBxH (mm)      52x6x39  
Stripped Length      10 mm

**Max Rated Cross Section**

Single Wire (solid)      0.2-4 mm<sup>2</sup>  
Stranded Wire (flexible)      0.2-2.5 mm<sup>2</sup>  
Wire Size      AWG 22-14

**SRSL 2.5-T32**



tightening torque/thread      0.7 Nm/M 2.5      Inspection Test Pattern Size      A 3

Type      Cat.-No.      Qty.p.pck.  
**SRSL 2.5-T32**      41055.2      green/yellow      100

**Ratings:**

**Dimensions**      TS 32  
LxBxH (mm)      42x6x52  
Stripped Length      10 mm

**Max Rated Cross Section**

Single Wire (solid)      0.2-4 mm<sup>2</sup>  
Stranded Wire (flexible)      0.2-2.5 mm<sup>2</sup>  
Wire Size      AWG 22-14