

△	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	△	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△						△					

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +85 °C(NOTE1)	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C
	VOLTAGE	500 V AC	APPLICABLE CONNECTOR	DF5A- * P-5DSA
	CURRENT	AWG18 8A	APPLICABLE CONTACT	DF5-1822SC(F)
		AWG20 6A		DF5A-1822SC(F)
	AWG22 5A	APPLICABLE CABLE	AWG18~AWG22	

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	×	×
MARKING	CONFIRMED VISUALLY.		×	×

ELECTRIC CHARACTERISTICS				
CONTACT RESISTANCE	100mA(DC OR 1000 Hz).	30mΩ MAX.	×	—
INSULATION RESISTANCE	500 V DC.	1000 MΩ MIN.	×	—
VOLTAGE PROOF	1500 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	×	—

MECHANICAL CHARACTERISTICS				
MECHANICAL OPERATION	30 TIMES INSERTIONS AND EXTRACTIONS.	①CONTACT RESISTANCE: 30 mΩ MAX. ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	×	—
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, - m/s ² AT 2h, FOR 3 DIRECTIONS.	①NO ELECTRICAL DISCONTINUITY OF 10μs.	×	—
SHOCK	490 m/s ² DURATION OF PULSE 11ms AT 3 TIMES FOR 3 DIRECTIONS.	②CONTACT RESISTANCE: 30mΩ MAX. ③NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	×	—

ENVIRONMENTAL CHARACTERISTICS				
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 →5~35→ 85 →5~35 °C TIME 30 →5 → 30 → 5 min UNDER 5 CYCLES.	①CONTACT RESISTANCE: 30 mΩ MAX. ②INSULATION RESISTANCE:1000 MΩ MIN. ③NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	×	—
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 ~ 95 %, 96 h.	①CONTACT RESISTANCE: 30 mΩ MAX. ②INSULATION RESISTANCE: 500 MΩ MIN. ③NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	×	—

REMARKS	NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT.	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
		I.DENPOUYA	I.DENPOUYA	H.Umehara	K. Katayama	
		'01.11.27	'01.11.27	'01.11.27	'01.11.30	

Note QT:Qualification Test AT:Assurance Test ×:Applicable Test

HIROSE ELECTRIC CO., LTD.	SPECIFICATION SHEET	PART NO.	DF5A- * S - 5 C
		CODE NO.(OLD)	CL
DRAWING NO.	ELC4-160243	PART NO.	CL676

TO

