


GAGE DIMENSIONS APPLY WHEN TOOL IS BOTTOMED BUT NOT UNDER PRESSURE. FOR REPLACEMENT OF PARTS OTHER THAN LISTED, TOOL SHOULD BE RETURNED TO OUR FACTORY TO INSURE PROPER CERTI-CRIMP ADJUSTMENT.



"W" DIM.	NO 60
.076	.082

QTY	DWG NUMBER	NAME	REMARKS	ITEM NO
2	21045-6	RING - RETAINING		6
1	300449	PIN - RETAINING		5
1	39364	SPRING		4
1	39366	COLLAR		3
2	300432	PIN - RETAINING		2
4	21045-3	RING - RETAINING		1

REV	DESCRIPTION	BY	CHK	DATE
F-1	REVISED	PZ		10-28-62
E	REVISED	BS		7-16-62
D	REVISED	BWS		4-15-62
C	REVISED	CM		3-27-62
B	REVISED	CM		3-27-62
A	REVISED	CM		3-27-62

49965	DESCRIPTION	49965
REQUIRED PER ASSEMBLY		

APPROVED: *[Signature]* 4-24-62
 DATE: 4-24-62
 BY: *[Signature]* 6-13-62
 DATE: 6-13-62

WIRE - RANGE - INSULATION: 12-10
 TOLERANCE EXCEPT AS NOTED: ± 1/16"
 SCALE: 1/1"
 TYPE: W FLAG
 LOC: M
 NO: 49965
 REV: F-1

AMP INCORPORATED
 HANDBOOK ASSEMBLY

8 7 6 5 4 3 2 1