



Technical specification:

Rated voltage: IEC 61076-2-101	4pos 160 V
Current rating: IEC 61076-2-101	4 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperatur range: IEC 60664-1	-30°C ... +70°C
Mating cycles: IEC 60512-9a	>=100

Materials:

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	PBT GF, UL 94
Coupling screw:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

Installation specification:

Recommended torque:	0,6 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 13: 36-000220

Contact assignment:

1	yellow
2	white
3	orange
4	blue
Shielding coupling screw	

Part no:	Description:	Length L:	Cable:
43-10944	SAL - 12D - RS4.2 - 2 / G6	2m	TPU, UL, green, 4xAWG22 Cable: 781-G63400
43-10945	SAL - 12D - RS4.2 - 3 / G6	3m	
43-10946	SAL - 12D - RS4.2 - 5 / G6	5m	
43-10947	SAL - 12D - RS4.2 - 10 / G6	10m	
43-xxxxx	SAL - 12D - RS4.2 - ... / G6	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: b 08.03.11 VF Ä3767 Coupling screw modified, spanner flats added, data sheet modified		title: Male connector M12x1 axial, Ethernet 100 MHz						
	tolerance of cable: L ≤ 4m: L + 40mm L > 4m: L + 1%			<table border="1"> <tr> <td>date</td> <td>name</td> </tr> <tr> <td>drawn 16.03.07</td> <td>Mankopf</td> </tr> <tr> <td>appd. 16.03.07</td> <td>Fromm</td> </tr> </table>	date	name	drawn 16.03.07	Mankopf	appd. 16.03.07
	date	name							
	drawn 16.03.07	Mankopf							
appd. 16.03.07	Fromm								
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH		dwg no: 43K1A243							
		part no: see table							