


THESE DRAWINGS ARE THE PROPERTY OF QUALTEK ELECTRONICS AND NOT TO BE REPRODUCED FOR OR COMMUNICATED TO A THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF AN OFFICER OF QUALTEK ELECTRONICS.



| REVISION |             |      |          |
|----------|-------------|------|----------|
| REV.     | DESCRIPTION | DATE | APPROVED |
|          |             |      |          |
|          |             |      |          |
|          |             |      |          |



WIRING:568B

| P1 | COLOR        | P2 |
|----|--------------|----|
| 1  | white/orange | 1  |
| 2  | orange       | 2  |
| 3  | white/green  | 3  |
| 6  | green        | 6  |
| 4  | blue         | 4  |
| 5  | white/blue   | 5  |
| 7  | white/brown  | 7  |
| 8  | brown        | 8  |

NOTE: ∞ TWISTED PAIR



**CONTROLLED**

NOTES:

- CABLE: CAT.5E UTP  
26AWG COPPER STRANDED WIRE. 4 TWISTED PAIRS, 30V, 60°C  
OUTER JACKET: COLOR: YELLOW, O.D.: 5.5 ± 0.2mm  
JACKET MATERIAL: PVC
- PLUG TYPE: MODULAR U.S.SHORT TYPE 8P8C GOLD PLATING 50u"  
MATERIAL: PC UL 94V-2  
S.R.: PVC 75P MOLD, COLOR: YELLOW
- PACKING: 1PC/POLYBAG
- RoHS COMPLIANT

| Dim range (mm) | Tolerance +/- (mm) | Qualtek Electronics Corp.<br>WCI DIVISION |                |                 |
|----------------|--------------------|---|----------------|-----------------|
|                |                    | Part Number:                              | 1225014-10     | RoHS Compliant  |
| 0-1            | 0.15               | Description:<br>CAT.5e UTP 8P8C - 8P8C    |                |                 |
| 1-6            | 0.20               |   |                |                 |
| 6-18           | 0.30               |   |                |                 |
| 18-50          | 0.50               |   |                |                 |
| 50-120         | 0.70               | UNIT: mm                                  |                |                 |
| 120-250        | 0.90               | Drawn / Date                              | Checked / Date | Approved / Date |
| 250-500        | 1.20               | R.Nuti<br>09-16-10                        | 09-16-10       | LY / 09-16-10   |