


DO NOT SCALE FROM THIS PRINT



**OPTION #1**  
-L: LOCKING LEAD (USE SC-1L1-GT: STYLE -S, -ZS ONLY)  
-2: STYLE -W ONLY (SEE TABLE 2)  
-3: STYLE -W ONLY (SEE TABLE 2)

**PLATING SPECIFICATION**  
-GG: GOLD/GOLD- SPECIFY -GG IN SOCKET SUFFIX -XX (NOT AVAILABLE ON -F & -K LEAD STYLE)  
-GT: GOLD/TIN- SPECIFY -GT IN SOCKET SUFFIX -XX (-F LEAD STYLE AVAILABLE FOR EXISTING CUSTOMERS ONLY) (-E LEAD STYLE EZ-2P3 AVAILABLE FOR EXISTING CUSTOMERS ONLY)  
-TT: TIN/TIN- SPECIFY -TT IN SOCKET SUFFIX -XX (STYLES -S, -ZS, -W, -ZW, -A, -C, -L, -M, -N ONLY)  
-ST: LOW GOLD/TIN - SPECIFY -ST IN SOCKET SUFFIX -XX(-S & -ZS ONLY)(ON -L OPTION USE SC-1L1-GT OR EZ-1L1-GT ONLY)  
-EE: EXTRA HEAVY GOLD/EXTRA HEAVY GOLD-SPECIFY -EE IN SOCKET SUFFIX -XX(STYLES -S & -ZS ONLY)  
-EG: EXTRA HEAVY GOLD/GOLD- SPECIFY -EG IN SOCKET SUFFIX -XX(STYLES -S & -ZS ONLY)  
-ET: EXTRA HEAVY GOLD/TIN- SPECIFY -ET IN SOCKET SUFFIX -XX(STYLES -S & -ZS ONLY)  
-GE: GOLD/EXTRA HEAVY GOLD- SPECIFY -GE IN SOCKET SUFFIX -XX(STYLES -S & -ZS ONLY)  
-TE: TIN/EXTRA HEAVY GOLD- SPECIFY -TE IN SOCKET SUFFIX -XX(STYLES -S & -ZS ONLY)

**NOTES:**

- MINIMUM PUSHOUT FORCES:  
ICA ASSEMBLY: 5 LBS.  
ICE ASSEMBLY: 10 LBS.  
ICO ASSEMBLY: 5 LBS.
- MAXIMUM ALLOWABLE BOW:  
.003 [.08] INCH PER INCH.
- GG PLATING OPTION NOT AVAILABLE ON SC-2P3-XX OR EZ-1S1-XX.  
-GT PLATING OPTION NOT AVAILABLE ON SC-1S1-XX, SC-1P3-XX, OR EZ-1S1-XX,
- GG PLATING OPTION AVAILABLE TO EXISTING CUSTOMERS ONLY ON EZ-2P3-XX.  
-GT PLATING OPTION AVAILABLE TO EXISTING CUSTOMERS ONLY ON SC-2P3-XX AND EZ-2P3-XX.

**TABLE 1** ( \* : CUT TO LENGTH IN FIG 1 )  
(\*\*\* = EXISTING CUSTOMERS ONLY)

SERIES	POSITION	ICA	ICA-H	ICO
-3	06	N/R	N/R	N/R
	08	SBOA-308	ICA-308-V	SBO-308
	10	N/R	N/R	N/R
	12	N/R	N/R	N/R
	14	SBOA-314	ICA-314-V	SBO-314
	16	SBOA-316	ICA-316-V	SBO-316
	18	SBOA-318	ICA-318-V	SBO-318
	20	SBOA-320	ICA-320-V	SBO-320
	22	SBOA-324*	ICA-322-V	SBO-324*
	24	SBOA-324	ICA-324-V	SBO-324
***28	ICA-328-V	ICA-328-V	N/R	
-4	22	SBOA-422	N/R	SBO-422
	24	N/R	N/R	N/R
-6	10	N/R	N/R	N/R
	14	N/R	N/R	N/R
	16	N/R	N/R	N/R
	18	N/R	N/R	N/R
	20	N/R	N/R	N/R
	22	N/R	N/R	N/R
	24	SBOA-624	ICA-624-V	SBO-624
	28	SBOA-628	ICA-628-V	SBO-628
	32	SBOA-632	ICA-632-V	SBO-632
	40	SBOA-640	ICA-640-V	SBO-640
48	SBOA-648	ICA-648-V	SBO-648	
-9	14	N/R	N/R	N/R
	24	N/R	N/R	N/R
	28	N/R	N/R	N/R
	32	N/R	N/R	N/R
	40	N/R	N/R	N/R
	48	N/R	N/R	N/R
	50	N/R	N/R	N/R
	64	N/R	N/R	N/R

**\* PROPRIETARY NOTE \***  
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSMITTED OR INCORPORATED IN ANY OTHER PRODUCT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.




FIGURE 1

REF. PART No.	'A'
ICA-322-XXX	1.100 [27.94]
ICO-322-XXX	1.100 [27.94]

**MATERIAL:**  
INSULATOR:  
BLACK G.F. POLYESTER  
UL RATED 94V-0  
SOCKET:  
CONTACT: 1/4 HARD BeCu  
SHELL: 1/2 HARD BRASS



EXISPROD\ASSEMBLY\DIP  
ICX-ASM1

520 PARK EAST BLVD. NEW ALBANY, INDIANA 47150  
PHONE (812) 944-6733 P.O. BOX 1147  
CODE 55322