


REV	DOCUMENT	CHANGED BY	CHECK
17	202843	GJW 12APR01	SAV
18	205953	TSM 9JUL02	SAV



CHARACTERISTICS	
OPERATING FORCE	8 OZ MAX
RELEASE FORCE	2 OZ MIN
DIFFERENTIAL TRAVEL	.006 - .016
OVERTRAVEL	.040 MIN
FREE POSITION	.625 MAX
RELEASE TRAVEL	.007 MIN

ELECTRICAL DATA	
CONTACT ARRANGEMENT S P N O	
L156 11A 1/3HP 125, 250 OR 277 VAC 1/2A 125 VDC, 1/4A 250 VDC 4A 125 VAC "L"	

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE:

	US (inch) CUSTOMARY	SI (mm) METRIC
NO PLACE	X ±.040	±1
ONE PLACE	.X ±.030	±0.4
TWO PLACE	.XX ±.015	±0.15
THREE PLACE	.XXX ±.005	±
ANGLES		±
RAW MATERIAL	COMMERCIAL STANDARD	

THIRD ANGLE PROJECTION

DRAWN	GJW	12APR01
CHECK	SAV	12APR01
THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.		
DIMENSIONS ARE TO BE MET BEFORE PROTECTIVE COATINGS ARE APPLIED		
PTC 2D	ASME Y14.5M-1994	

Honeywell			
TITLE SWITCH, BASIC			
SIZE	DWG TYPE	DRAWING NAME	REV
B	I	V3-123	18
SCALE 2 : 1		WEIGHT	SHEET 1 OF 1