

## Specification Sheet

Part Number: 170-03055



Braided Sleeving, Aluminum Laminated Fiberglass, .75" Dia, AL/GF, Silver, 250 ft/bulk reel

<b>Article Number</b>	170-03055
<b>Type</b>	BSHTTST34SRB
<b>Color</b>	Silver (SR)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.</li><li>• Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.</li><li>• Cuts with ordinary scissors for fast, easy application.</li></ul>
<b>Quantity Per</b>	reel
<b>Product Description</b>	A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.
<b>Short Description</b>	Braided Sleeving, Aluminum Laminated Fiberglass, .75" Dia, AL/GF, Silver, 250 ft/bulk reel

Global Part Name

BSHTTST34SRB-AL/GF-ML

Length L (Imperial)

250.0

Length L (Metric)

76.2

Bundle Diameter Min (Imperial)

0.1

Bundle Diameter Min (Metric)

2.54

Bundle Diameter Max (Imperial)

0.687

Bundle Diameter Max (Metric)

17.4

Diameter D (imperial)

0.75

Diameter D (metric)

19.1

Nominal Diameter (Imperial)

3/4

Nominal Diameter (Metric)

19.1

Wall Thickness WT (Imperial)

0.025

Wall Thickness WT (Metric)

0.64

Material

Aluminum (AL) Glass Fiber (GF)

Material Shortcut

AL GF

<b>Flammability</b>	Non-Flammable
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-76°F to +491°F (-60°C to +255°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	250
<b>Package Quantity (Metric)</b>	76.20
<b>Customs Number</b>	7019901000
<b>Weight (Metric)</b>	3.91
<b>Weight (Imperial)</b>	8.625