

**Industrial Ethernet
IE-PS-V04P-2SC-POF-BP**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



PushPull plug-in connector set according to IEC
61076-3-106 ver.4 (IEC24702), plastic with SC insert

General ordering data

Type	IE-PS-V04P-2SC-POF-BP
Order No.	1963390000
Version	FO connector, Version 4, SC-RJ POF, kink prevention, IP 67
GTIN (EAN)	4032248651863
Qty.	10 pc(s).

Data sheet

Industrial Ethernet IE-PS-V04P-2SC-POF-BP

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Net weight 56.2 g

Temperatures

Operating temperature -40 °C...70 °C Storage temperature
 Installation temperature

Downloads

GOST Approval	Installation video	STEADYTEC® assembly instruction SC-RJ - POF IP67 connector_EN_HD.mp4
POCC DE.ME25.B01411.pdf		

General data

Colour	Miscellaneous	Connection 1	SC
Connection 2	SC	Description of article	Version 4, SC-RJ POF, kink prevention
Fibre type	POF	Housing main material	PA UL 94 V0
Insertion loss	0.5 dB singlemode, 0.4 dB multimode, ≤ 1.0 dB POF	Plugging cycles	500
Protection degree	IP 67	Return loss (attenuation)	40 dB singlemode; 30 dB multimode
Sheath diameter, max.	10 mm	Sheath diameter, min.	5 mm

Standards

Connector standard IEC 61076-3-106 Var. 4,
IEC 61754-24

Classifications

ETIM 3.0	EC001121	ETIM 4.0	EC002641
ETIM 5.0	EC002641	ETIM 6.0	EC002641
UNSPSC	30-21-18-10	eClass 5.1	27-26-07-08
eClass 6.2	27-26-07-08	eClass 7.1	27-25-05-04

Approvals

Approvals



ROHS Conform

Data sheet

**Industrial Ethernet
IE-PS-V04P-2SC-POF-BP**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Dimensioned drawing

