


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 53.4 |
| B | 22.2 |
| C | 4 |
| D | 33.8 |
| E | 47.8 |
| F | 44.5 |
| G | 57 |
| H | 4.3 |


| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|---|
| 2 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 6 | KONTAKTBUCHSE / CONTACT SOCKET |
| 8 | DOSENGEHÄUSE / SHELL |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Specification and Dimensions subject to change
 Drawings illustrate normal insulator positioning

| Material Specification: | |
|-------------------------|---|
| Shell Material: | Aluminium alloy |
| Shell Plating: | Olive drab chromate over cadmium (conductive) |
| Insulator Material: | CR-Elastomere |
| Contact Material: | Copper alloy |
| Contact Plating: | Hard silver |

all dimensions are in mm
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m
 drawing for CUSTOMER

| | | |
|--|-------------|------------------------------------|
|  ITT <i>Engineered for life</i> <small>ITT CANNON GmbH D - 71384 Weinstadt/Germany</small> | description | CA3102E32-17S-B-F80-F0 |
| | | Box mounting receptacle |
| | | AWG Crimp / Socket / Layout: 32-17 |

© All rights reserved. Reproduction or issue to third in any form
 whoever is only permitted with written authorization of ITT Cannon  page 1/1 revision 1488 30. Jul 18