


ARR Indust X7R HT200C, Ceramic, 200C, 0.1 uF, 10%, 25 VDC, X7R, Commercial, High Temperature, Lead Spacing = 5.08mm



General Information	
Supplier:	KEMET
Series:	ARR Indust X7R HT200C
Style:	Radial
Description:	Commercial, High Temperature
Features:	Commercial
RoHS:	No
Termination:	Gold
Testing and Reliability:	Standard

Dimensions	
L	7.62mm MAX
H	7.62mm MAX
T	2.54mm MAX
S	5.08mm +/-0.38mm
LL	31.75mm MIN
F	0.51mm +/-0.05mm

Specifications	
Capacitance:	0.1 uF
Capacitance Tolerance:	10%
Voltage DC:	25 VDC
Temperature Range:	-55/+200C
Temperature Coefficient:	X7R

Packaging Specifications	
Packaging:	Bulk, Bag

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.